


[2017-July-NewsValid Braindump2go 300-375 Exam PDF and VCE 77Q Offer[Q61-Q68

2017/July CISCO 300-375 Exam Dumps with PDF and VCE New Updated in www.Braindump2go.com Today!100% 300-375 Real Exam Questions! 100% 300-375 Exam Pass Guaranteed! 1.|2017 New 300-375 Exam Dumps (PDF & VCE) 77Q&As Download:<https://www.braindump2go.com/300-375.html> 2.|2017 New 300-375 Exam Questions & Answers Download: <https://drive.google.com/drive/folders/0B75b5xYLjSSNR21JWVlyUWFaTWM?usp=sharing> QUESTION 61Which attribute on the Cisco WLC v7.0 does RADIUS IETF attribute "Tunnel-Private-Group ID" assign? A. ACLB. DSCPC. QoS. VLAN Answer: D QUESTION 62Which three WLAN polices can be controlled by using the Cisco IBNS on the Cisco WLC and Cisco Secure ACS? (Choose three.) A. QoS settingB. VLANC. EAP typeD. ACLE. authentication priority orderF. NAC state Answer: ABD QUESTION 63An engineer is securing the wireless network from vulnerabilities. Which four strategies are recommended for mitigation? (Choose four.) A. MFPB. identity-based networkingC. rogue locationD. EAP-TLSE. guest monitoringF. RF profilesG. rogue detectionH. password policies Answer: ACEG QUESTION 64Refer to the exhibit. A client reports being unable to log into the wireless network, which uses PEAPv2. Which two issues appear in the output? (Choose two.)



A. There is a problem with the client supplicant.B. The AP has the incorrect RADIUS server address.C. The AP has lost IP connectivity to the authentication server.D. The EAP client timeout value should be increased.E. The authentication server is misconfigured on the controller.F. The authentication server is misconfigured in the WLAN. Answer: AD QUESTION 65When using the Standalone Profile Editor in the Cisco AnyConnect v3.0 to create a new NAM profile, which two statements describe the profile becoming active? (Choose two.) A. selects the new profile from NAMB. selects "Network Repair" from NAMC. becomes active after a save of the profile nameD. ensures use of "configuration.xml" as the profile nameE. ensures use of "config.xml" as the profile nameF. ensures use of "nam.xml" as the profile name Answer: BD QUESTION 66Which feature should an engineer select to implement the use of VLAN tagging, QoS, and ACLs to clients based on RADIUS attributes? A. per-WLAN RADIUS source supportB. client profilingC. AAA overrideD. captive bypassingE. identity-based networking Answer: C QUESTION 67How should the Cisco Secure ACS v4.2 and the Cisco WLC v7.0 be configured to support wireless client authentication? A. The WLC configured for RADIUS and the Cisco Secure ACS configured for RADIUS (Cisco Aireospace)B. The WLC configured for RADIUS and the Cisco Secure ACS configured for RADIUS (IETF)C. The WLC configured for TACACS+ and the Cisco Secure ACS configured for TACACS+ (Cisco Aireospace)D. The WLC configured for TACACS+ and the Cisco Secure ACS configured for TACACS+ (Cisco IOS) Answer: A QUESTION 68Clients are failing EAP authentication. A debug shows that an EAPOL start is sent and the clients are then de-authenticated. Which two issues can cause this problem? (Choose two.) A. The WLC certificate has changed.B. The WLAN is not configured for the correct EAP supplicant type.C. The shared secret of the WLC and RADIUS server do not match.D. The WLC has not been added to the RADIUS server as a client.E. The clients are configured for machine authentication, but the RADIUS server is configured for user authentication. Answer: CD

!!!RECOMMEND!!! 1.|2017 New 300-375 Exam Dumps (PDF & VCE) 77Q&As Download: <https://www.braindump2go.com/300-375.html> 2.|2017 New 300-375 Study Guide Video: YouTube Video:

[YouTube.com/watch?v=nIOEU3zjhQY](https://www.youtube.com/watch?v=nIOEU3zjhQY)